




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61F 2/06	A1	(11) International Publication Number: WO 00/51522 (43) International Publication Date: 8 September 2000 (08.09.00)
(21) International Application Number: PCT/GB00/00732 (22) International Filing Date: 3 March 2000 (03.03.00) (30) Priority Data: 9904722.7 3 March 1999 (03.03.99) GB (71)(72) Applicant and Inventor: MURCH, Clifford, Rowan [GB/GB]; 20 Carrick Avenue, Ayr KA7 2SN (GB). (74) Agents: MCCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: INFLATABLE INTRALUMINAL GRAFT  (57) Abstract <p>A collapsible stent graft for aortic aneurysms comprises a collapsible inner tubular member (26) and an outer layer (24) fused or adhered thereto such as to provide a spiral inflatable member (22) therebetween. The stent graft is inserted into an artery in the collapsed state and then expanded into position by introducing a liquid into the inflatable member and sealing the member. The graft is held in place by an expandable stent (40).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INFLATABLE INTRALUMINAL GRAFT

TECHNICAL FIELD

5 This invention relates to intraluminal grafts. More particularly, this invention relates to intraluminal grafts useful as a lining for blood vessels or other body conduits.

BACKGROUND

10 Previously, the treatment of abdominal aortic aneurysms has involved using surgical grafts wherein the grafts are sutured into place. Conventional vascular grafts have long been used in humans and animals.

15 The treatment of abdominal aortic aneurysms requires a major surgical procedure to open the abdomen, excise the aneurysm sac and replace the vessel with a graft, which is sutured into place under direct vision. Many materials have been used to form the graft. At the present time this remains the preferred method of treatment for almost all abdominal aortic aneurysms.

20 Surgical graft materials such as flexible tubes of woven or knitted polyethylene terephthalate or porous polytetrafluoroethylene (PTFE) have previously been used. Grafts of biological origin have also been used; examples of these being fixed human umbilical or bovine arteries.

In the last few years, attempts have been made to reduce the extent of the surgical procedure by introducing these conventional, surgical grafts through the femoral arteries, passing them proximally, through the iliac arteries into the aorta and fixing them in place using endovascular stents, rather than sutures. These surgical grafts are large calibre devices which, even in their non-deployed state, are as large or even exceed the diameter of the iliac arteries through which they must pass. As the iliac arteries are often narrowed by, for example, atheromatous disease, the arteries may be damaged during introduction of the device.

More recently, interventional radiologists have attempted to improve on this concept using non-surgical graft material, catheters and endovascular stents to locate suitable vascular grafts or conduits onto the aortic aneurysm sac, from percutaneous punctures in the femoral arteries, requiring minimal surgical intervention. These techniques have become known as minimally invasive therapy.

A driving force to the development of the devices proposed in the present application has been the reduction in the size of the device when being inserted and also the reliability of the devices.

Although intraluminal devices are well-known in the field for the repair of inner linings for blood vessels or other body conduits, these previous types of devices are

constructed, for example, from a thin layer of PTFE wrapped around a housing which is capable of expansion. Examples of such housings include self-expanding or balloon expandable-type devices comprising a mesh-like structure.

5 Due to the mesh-like structures used in previously known stent grafts, there is a minimum diameter to which the device can be reduced on its full contraction. On average, the minimum to which these devices can be reduced is 7mm (21 French gauge) in diameter. There is therefore
0 a limitation of these types of devices, for example, for use in babies, small children and old people where any amount of abrasion on the inner lining of the blood vessel during insertion of the stent graft may cause rupture of the vessel. It can also prove troublesome to expand these
5 devices once inserted into the body. These types of grafts may also suffer from kinking which can result in the blocking of the passageway.

It is an object of at least one aspect of the present invention to mitigate one or more of the aforementioned
0 problems and disadvantages of the prior art.

It is therefore an object of the present invention to provide a kink resistant device capable of forming a lining for blood vessels or other body conduits.

SUMMARY OF THE INVENTION

According to one aspect of the present invention, there is provided a collapsible stent graft which comprises a collapsible tubular member for lining a blood vessel and an inflatable member extending around the tubular member and attached thereto whereby inflation of the inflatable member expands the tubular member from a collapsed state to an expanded state wherein in use it lines the blood vessel.

By collapsible herein is meant that the stent graft is capable of collapsing into a structure with a smaller cross-sectional area.

A stent graft is a structure capable of forming a lining in a body conduit which can be firmly secured within the conduit via a stenting procedure. The stent graft may or may not include an actual stent.

Preferably, the inflatable member is formed by partially fusing or adhering an outer layer to the collapsible tubular member so as to provide one or more inflatable members therebetween. Alternatively, a separate continuous inflatable member is fused or adhered onto the outer surface of the tubular member. The inflatable member preferably forms a spiral structure comprising a plurality of turns around the tubular member. The inflatable member is preferably 1-2mm in cross-sectional diameter with a spacing of 1-2 mm between adjacent turns of the inflatable

member measuring along the longitudinal length of the stent graft.

The inflatable member may also take a variety of other shapes such as a zig-zag or square-wave pattern around the tubular member.

There may be a plurality of inflatable members around the collapsible tubular member.

Preferably, a tube is attached to the proximal end of the inflatable member to allow inflation thereof. A further tube may also be attached to the distal end to allow preferential inflation thereof to locate the graft in the desired place. Any free ends of the inflatable channel are, of course, closed. The tube(s) may be removably attached by known means (one-way valve, screw etc.) to allow removal after use in such manner as to maintain the channel in the inflated state. Alternatively, one or both tubes could be integrally formed between the tubular member and outer layer.

A removable sheath may be provided around the stent graft to facilitate insertion into an artery and which is removed prior to expansion of the stent graft.

The material for inflating the inflatable member is preferably a low viscosity liquid so as to be easily injected, is radio-opaque to assist visualisation of the graft in vivo, able to set to form a gel-like substance, give flexibility to the graft, be non-toxic and adhere to

the inner and outer walls of the inflatable member to help prevent a tear of the inner layer causing dissection. Dissection is where the lining of the stent graft becomes torn and separated from the blood vessel leading to occlusion of the blood vessel and restriction in the flow of blood therein.

Suitable materials for inflation may be, for example, silicone-based liquids, elastomeric materials, plastics materials, or a thermoplastic or thermosetting resin mixture which may be solidified after injection. A chemically cured resin, such as cyanoacrylate resin ("superglue") may be used. A further suitable substance may, for example, be 2-hydroxyethyl methacrylate (HEMA). Silicone liquid satisfies some of the required criteria, but would not bond to the inner and outer surfaces of the inflatable member. However, this may not be a problem if polytetrafluoroethylene (PTFE) or other material sufficiently strong to resist tearing is used.

Any suitable length and diameter of collapsible tubular member may be used. The collapsible tubular member is of tubular shape generally with a thickness of at most 0.2mm and preferably thinner than 0.1mm and a cross-sectional diameter ranging from, for example, 25mm to 30mm. The collapsible tubular member may also be of a bifurcated form. The tubular member may also be tapered. In its

collapsed state the tubular member has a small cross-sectional diameter.

Preferably, the end of the collapsible tubular member has an undulating shape which helps to maximise the contact between the graft and the aorta of the patient, so as to accommodate different levels of the origins of the renal arteries from the aorta. Alternatively, the end may be angled.

Hooks on the stent, not at the inflatable sites, (as used with a Gianturco stent) may also be desirable for fixing the stent graft in place. As PTFE is suitable for suturing, this is ideal for this form of fixation. Markers on the graft are preferred so that the correct part of the graft is used for stenting.

Preferably, the stent graft is introduced in a collapsed state into the body conduit via a small puncture therein using a catheter. Preferably, the graft is wound round a central catheter, with the catheter shaft of the angioplasty balloon used to distend the proximal aortic stent, which would pass over a guide wire introduced initially by arterial puncture in the groin.

Preferably, the inflatable and collapsible tubular member is made from expanded PTFE. Generally, the thickness of this sheet is at most 0.1mm and preferably thinner. Uni-axially oriented films having a microstructure of uni-axially oriented fibrils wherein

substantially all of the fibrils are oriented parallel to each other may be used. Multi-axially oriented films having a microstructure of bi-axially or multi-axially oriented fibrils wherein the fibrils are oriented in at least two directions which are substantially perpendicular to each other may also be used.

If the graft is made of an inner and outer layer fused together and the inner layer is made of expanded PTFE, the outer layer need not necessarily be made of this material. Expanded PTFE is preferred as the inner material as this is a suitable graft material enabling ingrowth of endothelium. The outer layer may however preferably be made from a material which has improved strength and may be made from thinner material hence reducing the size of the device further. Suitable materials include nylon, polyethylene, polypropylene, polyurethane, polyvinylchloride and various fluoropolymers. The outer layer may even have the property of thrombogenicity which may be desirable as this would help to thrombose the aneurysm sac. A thromogenic material would encourage the blood in the aneurysm sac, outside the graft, to clot. Suitable thrombogenic coating materials include collagen, polysaccharides and blood clotting factors (e.g. thrombin and fibrinogen). This is beneficial, as it encourages the aneurysm sac to shrink and resolve. It is also possible to form the graft with small perforations, not within the region of the

inflatable member, which would allow ingrowth onto the PTFE from the outside of the graft.

One major problem with aortic stent grafts in general is the requirement for a neck of normal aorta below the renal arteries. This is used to facilitate the placement of the device and produces a seal. It is often the absence of a suitable neck that prevents the use of a stent graft from being attempted or results in failure of the device. This may occur at the time of placement, soon after or even months later.

The present invention enables the treatment of abdominal aortic aneurysms by a stent graft mechanism extending from the infra-renal segment of the aorta to either the distal aorta or into one of the iliac arteries. Via this technique, it may be possible to cross the renal arteries with graft material and subsequently revascularise the kidneys. An additional application may also be the treatment of thoracic aneurysms.

The possibility of providing a stent graft structure across the renal arteries so that their origins are covered by the graft material and then revascularising the kidneys is therefore a preferred function. It may be possible to achieve this with the present system because the graft material is very thin. Revascularisation would be achieved by percutaneous puncture in a branch of the renal artery within the kidney and puncturing the graft material from

the renal side into the aorta. Angioplasty and then stenting of the renal artery origin at this point would be performed from the groin re-establishing renal blood flow.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

5 Preferred embodiments of the invention will now be described by way of example with reference to the drawings in which:

Figure 1 is a side view of a conventional angioplasty balloon showing a balloon member inflated;

10 Figure 2 is a side view of a collapsible stent graft according to the present invention, comprising a spiral inflatable member and showing cross-sectional representations;

15 Figure 3 is a side view of the collapsible stent graft as shown in Figure 2 inflated and also shows cross-sectional representations;

Figure 4 is a view of the inflated device and how it fits into an infra-renal aorta;

20 Figure 5 is a representation of a preferred configuration of the upper end of a stent graft used to accommodate an asymmetric renal artery and to maximise the contact between the graft and aorta at this site;

25 Figure 6 is a representation of a further preferred angled configuration of the upper end of a stent graft used to accommodate an asymmetric renal artery and to maximise

the contact between the graft and aorta at this site; and

Figure 7 is a schematic representation of an assembly for insertion into an aorta of a patient.

Figure 1 shows a prior art angioplasty balloon 10 in an inflated form. At one end 14 of the balloon 10 a catheter 12 is fused to the balloon 10. Due to this fusion, such an angioplasty balloon is not suitable for the present invention as disconnection of the catheter 12 from the balloon 10 will cause the balloon 10 to rupture.

In Figure 2, is shown a stent graft 20 according to the present invention with a spiral inflatable member 22 capable of inflation formed from an inner tubular member 26 and an outer layer 24. The inflatable graft 20 comprises two fused ends 28, 30. Between alternate turns of the spiral inflatable member 22 the inner tubular member 26 and outer layer 24 are fused or adhered together. This fusion occurs by any suitable method, such as, adhesive bonding, welding, heat sealing or ultrasonic sealing. Longitudinal and transverse cross-sectional representations of the spiral inflatable member 22 are shown. The solid black line in Figure 2 shows the inner tubular member 26 and outer layer 24 fused together in such a way as to provide the spiral inflatable member 22 between two fused ends 28, 30. At cross-sections A, B, C, D, E and F along the spiral inflatable member, representations show the arrangement of the inflatable member 22.

In Figure 3, the spiral inflatable member 22 is shown inflated. The graft is inflated by injecting a suitable material into the inflatable member 22. The inflatable member 22 is connected at the distal end of the graft (that is the femoral end and the end nearest to where the graft is introduced into the femoral artery, with the graft in position within the aortic aneurysm) to a fine bore catheter tube of 1mm diameter (3 French gauge) through which a fluid-like material is injected. This requires a detachable valve mechanism to be located near the junction between the fine bore catheter and the inflatable member 22 to allow the fine bore catheter tube to be disconnected and for the inflatable member 22 to remain inflated without leakage. Alternatively, inflation could be initiated at the proximal end (the forward end) of the graft via separate catheter tube. The inflatable member 22 of the graft 20 acts like a spring system to extend the collapsed tubular member. On inflation the graft forms a predetermined shape. This predetermined shape may be tubular as shown in the Figures or bifurcated. The fused sections of the graft 20 between the turns of the inflated member 22 allows flexibility and prevents kinking and the development of dissection.

Figure 4 is a three-dimensional representation of the graft 20 in an inflated form in place in an infra-renal aorta. Stents 40 at each end hold the graft in place.

Figures 5 and 6 show possible configurations of an upper end 28, 30 of the graft 20 to accommodate asymmetric renal artery origins and to maximise the contact between the graft 20 and aorta at this site.

5 Figure 7 shows an assembly ready for introduction into an artery and comprising an angioplasty balloon 10 of the type shown in Figure 1 located within an expandable stent 40 (e.g. Palmaz stent). A collapsed stent graft 20 according to the present invention is located around
10 catheter 12 of the angioplasty balloon behind the stent. Alternatively, a self-expanding stent (e.g. a Wall stent or a Nitinol stent) could be employed. A sheath (not shown) may be provided around the assembly to facilitate insertion into the artery.

15 The insertion procedure is as follows. The assembly is introduced into the artery until the forward end 28 of the graft is in the correct position. The sheath (if any) is then partially retracted to reveal the forward end of the graft, which is then partially inflated by introduction
20 of liquid into the forward end thereof through a catheter tube 42 removably attached thereto.

This expands the forward end of the graft into contact with the artery wall and locates the graft in place.

The catheter is then partially withdrawn until the
25 stent lies within the expanded forward end 28 of the graft.

The angioplasty balloon is inflated to expand the stent to secure the graft to the arterial wall.

The sheath is then fully retracted to allow the rest of the graft to be inflated (after first removing the tube 42 if required). The angioplasty balloon is removed. The rearward end of the graft may then be stented in place in similar manner. Any tube attached to the rearward end of the inflatable member is now removed to leave the member in the inflated state.

CLAIMS

1. A collapsible stent graft, which comprises a collapsible tubular member for lining a blood vessel and an inflatable member extending around the tubular member and attached thereto, whereby inflation of the inflatable member expands the tubular member from a collapsed state to an expanded state.

2. A stent graft according to claim 1 wherein an outer layer is provided around the tubular member and is fused or adhered thereto so as to provide said inflatable member.

3. A stent graft according to claim 2 wherein the inner tubular member is formed of expanded polytetrafluoroethylene.

4. A stent graft according to claim 2 wherein the outer layer is formed of expanded polytetrafluoroethylene.

5. A stent graft according to claim 2, 3 or 4 wherein the outer layer is thrombogenic so as to encourage clotting of surrounding blood.

6. A stent graft according to any preceding claim wherein the inflatable member forms a spiral structure comprising a plurality of turns around the tubular member.

7. A stent graft according to claim 6 wherein there is a spacing of 1 to 2mm between adjacent turns.

8. A stent graft according to any of claims 1 to 6 wherein the inflatable member is in the form of a zig-zag or square-wave pattern around the tubular member.

9. A stent graft according to any preceding claim provided with perforations, not within a region of the inflatable member, to allow ingrowth thereinto.

10. A stent graft according to any preceding claim wherein the tubular member has a wall thickness thinner than 0.1mm.

11. A stent graft according to any preceding claim wherein an end of the tubular member is of undulating shape.

12. A stent graft according to any of claims 1 to 10 wherein an end of the tubular member is angled.

13. A stent graft according to any preceding claim wherein the tubular member is bifurcated.

14. A stent graft according to any preceding claim wherein the inflatable member contains a liquid for inflation thereof.

15. A stent graft according to claim 14 wherein the liquid is a resin which solidifies after injection into the inflatable member.

16. A stent graft according to claim 14 wherein the resin adheres to the inside walls of the inflatable member.

17. A stent graft according to any preceding claim which further comprises a stent having hooks for fixing the stent graft in place.

1/2




Fig. 1




Fig. 2




Fig. 3

2/2




Fig. 4




Fig. 5




Fig. 6




Fig. 7

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/00732

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 871 537 A (THOMETZ DARLENE A ET AL) 16 February 1999 (1999-02-16) figures 1-12 column 2, line 58 -column 4, line 47 claims 1-12 ---	1,6,8, 13-17
X	WO 98 55047 A (SAMUELS SHAUN L W) 10 December 1998 (1998-12-10) figure 1 page 5, paragraph 1 - paragraph 4 page 6, paragraph 2 -page 7, paragraph 2 page 9, paragraph 3 ---	1
A	---	15,16
P,X	WO 99 39662 A (TRIAD VASCULAR SYSTEMS INC) 12 August 1999 (1999-08-12) figures 1-6 page 11, line 18 -page 18, line 16 ---	1-4,6,7, 10-14
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 June 2000

Date of mailing of the international search report

20/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mary, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/00732

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 411 550 A (HERWECK STEVE A ET AL) 2 May 1995 (1995-05-02) figures 4,7 column 2, line 50 - line 65 column 5, line 1 -column 6, line 21 column 9, line 11 - line 21 ---</p>	9
A	<p>US 5 499 995 A (TEIRSTEIN PAUL S) 19 March 1996 (1996-03-19) column 6, line 29 - line 65 column 2, line 59 - line 67 claims 1,21 -----</p>	5

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 00/00732

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5871537 A	16-02-1999	EP 0959810 A WO 9729716 A US 6059823 A	01-12-1999 21-08-1997 09-05-2000
WO 9855047 A	10-12-1998	NONE	
WO 9939662 A	12-08-1999	AU 2663699 A	23-08-1999
US 5411550 A	02-05-1995	AU 676666 B AU 2656292 A CA 2119252 A EP 0604546 A JP 7501956 T WO 9305730 A	20-03-1997 27-04-1993 01-04-1993 06-07-1994 02-03-1995 01-04-1993
US 5499995 A	19-03-1996	AU 2605495 A CA 2191091 A EP 0788391 A JP 10500873 T WO 9532018 A	18-12-1995 30-11-1995 13-08-1997 27-01-1998 30-11-1995